

**SAFETY DATA SHEET**

TIMBABUILD EWS BASE

Page 1

Issued: 06/12/2004

Revision No: 1

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: TIMBABUILD EWS BASE
Company name: Chemfix Products Ltd
Mill Street East
Dewsbury
West Yorkshire
WF12 9BQ
United Kingdom
Tel: 01924 453886
Fax: 01924 431658

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: BISPHENOL A/F - EPOXY RESIN 70-90%
CAS: 40216--08-8
[Xi] R36/38; [Sens.] R43; [N] R51/53

- OXIRANE, MONO[(C12-14ALKYLOXY)METHYL] DERIVATIVES 10-30%
EINECS: 271-846-8 CAS: 68609-97-2
[Xi] R38; [Sens.] R43
- 1,6-HEXANEDIOLGLYCIDYLETHER 1-10%
EINECS: 240-260-4 CAS: 16096-31-4
[Xi] R36/38; [Sens.] R43; [-] R52/53

3. HAZARDS IDENTIFICATION

Main hazards: Irritating to eyes and skin. May cause sensitisation by skin contact. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.
Eye contact: There may be irritation and redness.
Ingestion: There may be soreness and redness of the mouth and throat.
Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

4. FIRST AID MEASURES (ACTION)

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.
Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.
Ingestion: Do not induce vomiting. Wash out mouth with water. Consult a doctor.
Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Carbon dioxide. Dry chemical powder. Alcohol or polymer foam.

Exposure hazards: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details.

Environmental precautions: Do not discharge into drains or rivers.

Clean-up procedures: Transfer to a closable, labelled salvage container for disposal by an appropriate method.

7. HANDLING AND STORAGE

Handling requirements: Ensure there is sufficient ventilation of the area.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.

Eye protection: Safety goggles. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid

Colour: Green

Odour: Barely perceptible odour

Evaporation rate: Negligible

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Insoluble

Also soluble in: Most organic solvents.

Viscosity: Non-viscous

Boiling point/range°C: >200

Flash point°C: >100

Relative density: 1.10

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to avoid: Heat.

Materials to avoid: Amines.

SAFETY DATA SHEET

TIMBABUILD EWS BASE

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.**11. TOXICOLOGICAL INFORMATION****Hazardous ingredients:** OXIRANE, MONO[(C12-14ALKYLOXY)METHYL] DERIVATIVES
ORL RAT LD50 17100 mg/kg**Chronic toxicity:** May cause sensitisation by skin contact.**Routes of exposure:** Refer to section 4 of SDS for routes of exposure and corresponding symptoms.**12. ECOLOGICAL INFORMATION****Mobility:** Insoluble in water. Heavier than water.**Persistence and degradability:** Not biodegradable.**13. DISPOSAL CONSIDERATIONS****NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.**14. TRANSPORT INFORMATION****ADR / RID**

UN no:	3082	ADR Class:	9
Packing group:	III	Classification code:	M6
Shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL A/F - EPOXY RESIN)		
Labelling:	9	Hazard ID no:	90

**IMDG / IMO**

UN no:	3082	Class:	9
Packing group:	III	EmS:	F-A,S-F
Marine pollutant:	.	Labelling:	9

IATA / ICAO

UN no:	3082	Class:	9
Packing group:	III	Packing instructions:	914
Labelling:	9		

15. REGULATORY INFORMATION**Hazard symbols:** Irritant.
Dangerous for the environment.

SAFETY DATA SHEET

TIMBABUILD EWS BASE



Risk phrases: R36/38: Irritating to eyes and skin.
R43: May cause sensitisation by skin contact.
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases: S2: Keep out of the reach of children.
S24: Avoid contact with skin.
S29: Do not empty into drains.
S37: Wear suitable gloves.
S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

Precautionary phrases: Contains epoxy constituents. See information supplied by the manufacturer.

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Risk phrases used in s.2: R36/38: Irritating to eyes and skin.
R43: May cause sensitisation by skin contact.
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R38: Irritating to skin.
R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.