METOBOND BASE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 22/06/2011 Revision date: 07/05/2025 Supersedes version of: 05/06/2024 Version: 4.3

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	:	Mixture
Name	:	METOBOND BASE
UFI	:	SJ0U-84T0-M00M-W9E6
Product code	:	54168
Type of product	:	Building and Repair application
Product group	:	Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Main use category	:	Industrial use,Professional use
Use of the substance/mixture	:	Building and construction work
Function or use category	:	Building and construction work

1.3. Details of the supplier of the safety data sheet

Manufacturer
Chemfix Products Ltd
Mill Street East
Dewsbury
WF12 9BQ West Yorkshire
England
T +44 (0)1924 453886/+34 872 729 763, F +44 (0)1924 458995
sds@chemfix.co.uk

Only Representative
Chemfix Products Limited
A Briolf Group Company
Ctra. N-II, km 706,5
17457 RIUDELLOTS DE LA SELVA (Girona)
SPAIN
T +34 872 729 763, F +44 (0)1924 458995
sds@chemfix.co.uk, www.chemfix.co.uk

1.4. Emergency telephone number

Emergency number : UK Manufacturer +44 (0)1924 431679 / Emergency Number Association (EENA) : 112 / CHEMTREC Ireland +353 1 901 46700

Country/Area	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals-24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Skin sensitisation, Category 1	H317
Reproductive toxicity, Category 1B	H360F
Specific target organ toxicity – Repeated exposure, Category 2	H373
Hazardous to the aquatic environment – Chronic Hazard, Category 2	H411

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

May damage fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :

GHS07 GHS08 GHS09

Signal word (CLP) : Danger

Contains : BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE.; BISPHENOL F-(EPICHLORHYDRIN), EPOXY RESIN.; OXIRANE, MONO[(C12-14ALKYLOXY)METHYL] DERIVATIVES.; QUARTZ (FINE FRACTION)

Hazard statements (CLP) : H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H360F - May damage fertility.
H373 - May cause damage to organs (lungs) through prolonged or repeated exposure.
H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (CLP) : P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P260 - Do not breathe dust/fume/gas/mist/vapours/spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P272 - Contaminated work clothing should not be allowed out of the workplace.
P273 - Avoid release to the environment.

2.3. Other hazards

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

Component	
Substance(s) not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605	BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE. (1675-54-3)

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE.	CAS-No.: 1675-54-3 EC-No.: 216-823-5 EC Index-No.: 603-073-00-2 REACH-no: 01-2119456619-26	20 – 30	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
BISPHENOL F-(EPICHLORHYDRIN), EPOXY RESIN.	EC-No.: 701-263-0 REACH-no: 01-2119454392-40	10 – 20	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
OXIRANE, MONO[(C12-14ALKYLOXY)METHYL] DERIVATIVES.	CAS-No.: 68609-97-2 EC-No.: 271-846-8 EC Index-No.: 603-103-00-4 REACH-no: 01-2119485289-22	3 – 10	Skin Irrit. 2, H315 Skin Sens. 1, H317 Repr. 1B, H360F
QUARTZ (FINE FRACTION) substance with a Community workplace exposure limit	CAS-No.: 14808-60-7 EC-No.: 238-878-4 REACH-no: Exempted in accordance with Annex V.7	1 – 3	STOT RE 1, H372

Specific concentration limits:		
Name	**Product identifier**	**Specific concentration limits (%)**
BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE.	CAS-No.: 1675-54-3 EC-No.: 216-823-5 EC Index-No.: 603-073-00-2 REACH-no: 01-2119456619-26	(5 ≤ C ≤ 100) Eye Irrit. 2; H319 (5 ≤ C ≤ 100) Skin Irrit. 2; H315

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

First-aid measures for first aider : First aid workers will be equipped with suitable personal protective equipment.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : Dust of the product, if present, may cause respiratory irritation after excessive inhalation exposure. Although no appropriate human or animal health effects data are known to exist, this material is expected to be an inhalation hazard.

Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.

Symptoms/effects after eye contact : Eye irritation.

Symptoms/effects after ingestion : None under normal conditions.

Chronic symptoms : May damage fertility or the unborn child.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	:	No fire hazard.
Explosion hazard	:	No direct explosion hazard.
Hazardous decomposition products in case of fire	:	Toxic fumes may be released.

5.3. Advice for firefighters

Firefighting instructions	:	Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	:	Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	:	Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.

For non-emergency personnel

Protective equipment	:	Wear recommended personal protective equipment.
Emergency procedures	:	Only qualified personnel equipped with suitable protective equipment may intervene. Do not breathe dust/fume/gas/mist/vapours/spray.

For emergency responders

Protective equipment	:	Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	:	Evacuate unnecessary personnel.

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment	:	Collect spillage.
Methods for cleaning up	:	Mechanically recover the product. Notify authorities if product enters sewers or public waters.
Other information	:	Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed	:	Not expected to present a significant hazard under anticipated conditions of normal use.
Precautions for safe handling	:	Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.
Hygiene measures	:	Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	:	Keep in a cool, well-ventilated place away from heat.
Storage conditions	:	Store locked up.
Packaging materials	:	Store always product in container of same material as original container.

7.3. Specific end use(s)

Building and construction work.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

National occupational exposure and biological limit values

QUARTZ (FINE FRACTION) (14808-60-7)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Silica crystaline (Quartz)
IOEL TWA	0.05 mg/m³ (respirable dust)
Remark	(Year of adoption 2003)
Regulatory reference	SCOEL Recommendations
Ireland - Occupational Exposure Limits	
Local name	Quartz, respirable dust
OEL TWA	0.1 mg/m³
Remark	BOELV (Binding Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2024

DNEL and PNEC

BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE. (1675-54-3)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	0.75 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	4.93 mg/m³
DNEL/DMEL (General population)	
Long-term - systemic effects,oral	0.5 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	0.87 mg/m³
Long-term - systemic effects, dermal	89.3 µg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	0.006 mg/l
PNEC aqua (marine water)	0.0006 mg/l
PNEC aqua (intermittent, freshwater)	0.018 mg/l
PNEC aqua (intermittent, marine water)	0.0018 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	0.341 mg/kg dwt
PNEC sediment (marine water)	0.0341 mg/kg dwt
PNEC (Soil)	
PNEC soil	0.0647 mg/kg dwt
PNEC (Oral)	
PNEC oral (secondary poisoning)	11 mg/kg food

BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE. (1675-54-3)	
PNEC (STP)	
PNEC sewage treatment plant	10 mg/l

BISPHENOL F-(EPICHLORHYDRIN), EPOXY RESIN.	
DNEL/DMEL (Workers)	
Acute - local effects, dermal	8.3 µg/cm²
Long-term - systemic effects, dermal	104.15 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	29.39 mg/m³
DNEL/DMEL (General population)	
Long-term - systemic effects,oral	6.25 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	8.7 mg/m³
Long-term - systemic effects, dermal	62.5 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	0.003 mg/l
PNEC aqua (marine water)	0.0003 mg/l
PNEC aqua (intermittent, freshwater)	0.0254 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	0.294 mg/kg dwt
PNEC sediment (marine water)	0.0294 mg/kg dwt
PNEC (Soil)	
PNEC soil	0.237 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	10 mg/l

OXIRANE, MONO[(C12-14ALKYLOXY)METHYL] DERIVATIVES. (68609-97-2)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	1 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	3.6 mg/m³
DNEL/DMEL (General population)	
Long-term - systemic effects,oral	0.5 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	0.87 mg/m³
Long-term - systemic effects, dermal	0.5 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	0.1058 mg/l
PNEC aqua (marine water)	0.01058 mg/l
PNEC aqua (intermittent, freshwater)	0.072 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	307.16 mg/kg dwt
PNEC sediment (marine water)	30.72 mg/kg dwt

OXIRANE, MONO[(C12-14ALKYLOXY)METHYL] DERIVATIVES. (68609-97-2)	
PNEC (Soil)	
PNEC soil	1.234 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	10 mg/l

8.2. Exposure controls

Appropriate engineering controls

Appropriate engineering controls:
Ensure good ventilation of the work station.

Personal protection equipment

Personal protective equipment:
Wear recommended personal protective equipment.
Personal protective equipment symbol(s):

Eye and face protection

Eye protection:
Safety glasses

Skin protection

Skin and body protection:
Wear suitable protective clothing

Hand protection:
Chemical resistant gloves (according to European standard ISO 374-1 or equivalent)

Hand protection					
Type	**Material**	**Permeation**	**Thickness (mm)**	**Penetration**	**Standard**
Disposable gloves, Reusable gloves	Nitrile rubber (NBR), Butyl rubber, Viton® II	6 (> 480 minutes)	0.4	As the product is a preperation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.	EN ISO 374

Respiratory protection

Respiratory protection:
In case of insufficient ventilation, wear suitable respiratory equipment. EN141. [In case of inadequate ventilation] wear respiratory protection.

Environmental exposure controls

Environmental exposure controls:
Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	:	Solid
Colour	:	Off-white.
Appearance	:	Paste.
Odour	:	Characteristic odour.
Odour threshold	:	Not available
Melting point	:	Not available
Freezing point	:	Not applicable
Boiling point	:	> 200 °C
Flammability	:	Non flammable.
Lower explosion limit	:	Not applicable
Upper explosion limit	:	Not applicable
Flash point	:	> 100 °C
Auto-ignition temperature	:	Not applicable
Decomposition temperature	:	Not available
pH	:	Not available
pH solution	:	Not available
Viscosity, kinematic	:	Not applicable
Solubility	:	Material insoluble in water.
Partition coefficient n-octanol/water (Log Kow)	:	Not available
Vapour pressure	:	Not available
Vapour pressure at 50°C	:	Not available
Density	:	1.5
Relative density	:	Not available
Relative vapour density at 20°C	:	Not applicable
Particle size	:	Not available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE. (1675-54-3)	
LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))
LD50 dermal	23000 mg/kg

BISPHENOL F-(EPICHLORHYDRIN), EPOXY RESIN.	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), Remarks on results: other:
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Remarks on results: other:

OXIRANE, MONO[(C12-14ALKYLOXY)METHYL] DERIVATIVES. (68609-97-2)	
LD50 oral rat	17100 mg/kg Source: Corporate Solution From Thomson Micromedex

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitisation : May cause an allergic skin reaction.
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE. (1675-54-3)	
NOAEL (chronic, oral, animal/male, 2 years)	15 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies), Guideline: EPA OPPTS 870.4300 (Combined Chronic Toxicity / Carcinogenicity), Guideline: other:, Remarks on results: other:
NOAEL (chronic, oral, animal/female, 2 years)	100 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies), Guideline: EPA OPPTS 870.4300 (Combined Chronic Toxicity / Carcinogenicity), Guideline: other:, Remarks on results: other:
IARC group	3 - Not classifiable

QUARTZ (FINE FRACTION) (14808-60-7)	
IARC group	1 - Carcinogenic to humans

Reproductive toxicity : May damage fertility.

OXIRANE, MONO[(C12-14ALKYLOXY)METHYL] DERIVATIVES. (68609-97-2)	
NOAEL (animal/male, F0/P)	10 mg/kg bodyweight Animal: Rat, Oral, OECD Guideline 443
NOAEL (animal/female, F0/P)	200 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: EPA OTS 798.4420 (Preliminary Developmental Toxicity Screen)
NOAEL (animal/female, F1)	200 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: EPA OTS 798.4420 (Preliminary Developmental Toxicity Screen)

STOT-single exposure : Not classified
STOT-repeated exposure : May cause damage to organs (lungs) through prolonged or repeated exposure.

BISPHENOL F-(EPICHLORHYDRIN), EPOXY RESIN.	
NOAEL (oral, rat, 90 days)	≈ 250 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)

QUARTZ (FINE FRACTION) (14808-60-7)	
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

METOBOND BASE	
Viscosity, kinematic	Not applicable

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short–term (acute) : Not classified
Hazardous to the aquatic environment, long–term (chronic) : Toxic to aquatic life with long lasting effects.

BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE. (1675-54-3)	
LC50 - Fish [1]	1.2 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Other aquatic organisms [1]	1.8 mg/l
EC50 72h - Algae [1]	9.4 mg/l Test organisms (species): Scenedesmus capricornutum
EC50 72h - Algae [2]	> 11 mg/l Test organisms (species): Scenedesmus capricornutum
LOEC (chronic)	1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0.3 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

BISPHENOL F-(EPICHLORHYDRIN), EPOXY RESIN.	
LC50 - Fish [1]	> 1000 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
LC50 - Fish [2]	5.7 mg/l Test organisms (species): Leuciscus idus
EC50 - Crustacea [1]	3.5 mg/l Test organisms (species): Daphnia magna
LOEC (chronic)	1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0.3 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

OXIRANE, MONO[(C12-14ALKYLOXY)METHYL] DERIVATIVES. (68609-97-2)	
NOEC chronic fish	100 mg/l
NOEC chronic algae	500 mg/l

12.2. Persistence and degradability

METOBOND BASE	
Persistence and degradability	Not rapidly degradable

BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE. (1675-54-3)	
Persistence and degradability	Not rapidly degradable

BISPHENOL F-(EPICHLORHYDRIN), EPOXY RESIN.	
Persistence and degradability	Not rapidly degradable

OXIRANE, MONO[(C12-14ALKYLOXY)METHYL] DERIVATIVES. (68609-97-2)	
Persistence and degradability	Rapidly degradable

QUARTZ (FINE FRACTION) (14808-60-7)	
Persistence and degradability	Not rapidly degradable

12.3. Bioaccumulative potential

BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE. (1675-54-3)	
Partition coefficient n-octanol/water (Log Pow)	3.84 Source: HSDB

12.4. Mobility in soil

OXIRANE, MONO[(C12-14ALKYLOXY)METHYL] DERIVATIVES. (68609-97-2)	
Mobility in soil	12830 Source: Quantitative Structure Activity Relation

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional waste regulation : Disposal must be done according to official regulations.
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations : Disposal must be done according to official regulations.
Product/Packaging disposal recommendations : Comply with applicable regulations for solid waste disposal. Disposal must be done according to official regulations.
Additional information : Do not re-use empty containers.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 3077	UN 3077	UN 3077	UN 3077	UN 3077

ADR	IMDG	IATA	ADN	RID
14.2. UN proper shipping name				
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (BIS-[4-(2,3-EPOXIPROPOXI)PHENYL] PROPANE. ; BISPHENOL F-(EPICHLORHYDRIN), EPOXY RESIN.)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (BIS-[4-(2,3-EPOXIPROPOXI)PHENYL] PROPANE. ; BISPHENOL F-(EPICHLORHYDRIN), EPOXY RESIN.)	Environmentally hazardous substance, solid, n.o.s. (BIS-[4-(2,3-EPOXIPROPOXI)PHENYL] PROPANE. ; BISPHENOL F-(EPICHLORHYDRIN), EPOXY RESIN.)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (BIS-[4-(2,3-EPOXIPROPOXI)PHENYL] PROPANE. ; BISPHENOL F-(EPICHLORHYDRIN), EPOXY RESIN.)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (BIS-[4-(2,3-EPOXIPROPOXI)PHENYL] PROPANE. ; BISPHENOL F-(EPICHLORHYDRIN), EPOXY RESIN.)
Transport document description				
UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (BIS-[4-(2,3-EPOXIPROPOXI)PHENYL] PROPANE. ; BISPHENOL F-(EPICHLORHYDRIN), EPOXY RESIN.), 9, III, (-)	UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (BIS-[4-(2,3-EPOXIPROPOXI)PHENYL] PROPANE. ; BISPHENOL F-(EPICHLORHYDRIN), EPOXY RESIN.), 9, III, MARINE POLLUTANT	UN 3077 Environmentally hazardous substance, solid, n.o.s. (BIS-[4-(2,3-EPOXIPROPOXI)PHENYL] PROPANE. ; BISPHENOL F-(EPICHLORHYDRIN), EPOXY RESIN.), 9, III	UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (BIS-[4-(2,3-EPOXIPROPOXI)PHENYL] PROPANE. ; BISPHENOL F-(EPICHLORHYDRIN), EPOXY RESIN.), 9, III	UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (BIS-[4-(2,3-EPOXIPROPOXI)PHENYL] PROPANE. ; BISPHENOL F-(EPICHLORHYDRIN), EPOXY RESIN.), 9, III
14.3. Transport hazard class(es)				
9	9	9	9	9
14.4. Packing group				
III	III	III	III	III
14.5. Environmental hazards				
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes EmS-No. (Fire): F-A EmS-No. (Spillage): S-F	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
No supplementary information available				

14.6. Special precautions for user

Overland transport

Classification code (ADR)	:	M7
Special provisions (ADR)	:	274, 335, 375, 601
Limited quantities (ADR)	:	5kg
Excepted quantities (ADR)	:	E1
Packing instructions (ADR)	:	P002, IBC08, LP02, R001
Special packing provisions (ADR)	:	PP12, B3
Mixed packing provisions (ADR)	:	MP10
Portable tank and bulk container instructions (ADR)	:	T1, BK1, BK2, BK3
Portable tank and bulk container special provisions (ADR)	:	TP33
Tank code (ADR)	:	SGAV, LGBV
Vehicle for tank carriage	:	AT
Transport category (ADR)	:	3
Special provisions for carriage - Packages (ADR)	:	V13

Special provisions for carriage - Bulk (ADR)	:	VC1, VC2
Special provisions for carriage - Loading, unloading and handling (ADR)	:	CV13
Hazard identification number (Kemler No.)	:	90
Orange plates	:	
Tunnel restriction code (ADR)	:	-

Transport by sea

Special provisions (IMDG)	:	274, 335, 966, 967, 969
Limited quantities (IMDG)	:	5 kg
Excepted quantities (IMDG)	:	E1
Packing instructions (IMDG)	:	LP02, P002
Special packing provisions (IMDG)	:	PP12
IBC packing instructions (IMDG)	:	IBC08
IBC special provisions (IMDG)	:	B3
Tank instructions (IMDG)	:	BK1, BK2, BK3, T1
Tank special provisions (IMDG)	:	TP33
Stowage category (IMDG)	:	A
Stowage and handling (IMDG)	:	SW23

Air transport

PCA Excepted quantities (IATA)	:	E1
PCA Limited quantities (IATA)	:	Y956
PCA limited quantity max net quantity (IATA)	:	30kgG
PCA packing instructions (IATA)	:	956
PCA max net quantity (IATA)	:	400kg
CAO packing instructions (IATA)	:	956
CAO max net quantity (IATA)	:	400kg
Special provisions (IATA)	:	A97, A158, A179, A197, A215
ERG code (IATA)	:	9L

Inland waterway transport

Classification code (ADN)	:	M7
Special provisions (ADN)	:	274, 335, 375, 601
Limited quantities (ADN)	:	5 kg
Excepted quantities (ADN)	:	E1
Carriage permitted (ADN)	:	T* B**
Equipment required (ADN)	:	PP, A***
Number of blue cones/lights (ADN)	:	0
Additional requirements/Remarks (ADN)	:	* Only in the molten state. ** For carriage in bulk see also 7.1.4.1. *** Only in the case of transport in bulk.

Rail transport

Classification code (RID)	:	M7
Special provisions (RID)	:	274, 335, 375, 601
Limited quantities (RID)	:	5kg
Excepted quantities (RID)	:	E1
Packing instructions (RID)	:	P002, IBC08, LP02, R001
Special packing provisions (RID)	:	PP12, B3
Mixed packing provisions (RID)	:	MP10
Portable tank and bulk container instructions (RID)	:	T1, BK1, BK2, BK3
Portable tank and bulk container special provisions (RID)	:	TP33
Tank codes for RID tanks (RID)	:	SGAV, LGBV
Transport category (RID)	:	3
Special provisions for carriage – Packages (RID)	:	W13
Special provisions for carriage – Bulk (RID)	:	VC1, VC2
Special provisions for carriage - Loading, unloading and handling (RID)	:	CW13, CW31

Colis express (express parcels) (RID) : CE11
Hazard identification number (RID) : 90

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.2. Chemical safety assessment

No chemical safety assessment has been carried out
For the following substances of this mixture a chemical safety assessment has been carried out:
BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE.
BISPHENOL F-(EPICHLORHYDRIN), EPOXY RESIN.
OXIRANE, MONO[(C12-14ALKYLOXY)METHYL] DERIVATIVES.

SECTION 16: Other information

Indication of changes

Section	Changed item	Comments
8.1	Additional information	**Added** DNEL/PNEC

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road

Abbreviations and acronyms:	
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer :
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disruptor

Full text of H- and EUH-statements:	
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Repr. 1B	Reproductive toxicity, Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2

Full text of H- and EUH-statements:	
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H360F	May damage fertility.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs (lungs) through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.